

K

K

24V AC/DC
0.85~1.1
50Hz~60Hz
≤1.5 W/24V DC ≤4.8 VA/24V AC

≤50mA/24V DC
≤15Ω
(EN 574 Type III C)

$$3\text{NO} + 1\text{NC} \quad 2\text{NO} + 2\text{NC}$$
$$\text{AgSnO}_2 + 0.2 \mu\text{mAu}$$

AC-15 5A/230V DC-13 5A/24V
10A gL/gG(NO) 6A gL/gG(NC)

数


- ≤30ms
- ≤15ms
- ≤250ms
- ≤500ms
- 20ms

境 数

IEC/EN 60947 IEC 61326-3-1
IEC/EN 61000-6-2 IEC/EN 61000-6-4
250 V AC
6000V (1.2/50μs)
1500 V AC 1min
IEC 60947-1
10Hz~55Hz 0.35mm
III

le = 1A 1 NO 7000000
B_{10d} 50%


► 功能框图



NPFSR-K322D

× × : 23mm×100mm×115mm


→ 应用示例



说明

- S1/S2 EN574 type IIIC
- KM1/KM2 IEC 60947

→ 功能描述



- “PWR”
- 0.5s S1 S2
- S1 S2


→ 安装

- DIN IEC 60715 35mm


-

A.


DIN




B.



C.



-



→ 面板显示

- PWR: ()
- K1: K1 () K1
- K2: K2 () K2

→ 注意事项

- IP20 ()

- IEC 60664-1 2

- IEC 61000-4

-

-

→ 补充说明

-