



	24V DC
	0.85 ~ 1.1
	≤ 2W/24V DC
	≤ 80mA/24V DC
	≤ 4ms
	≤ 15Ω
	4NO+2NC
	AgSnO ₂ +0.2μmAu
	AC-15: 5A/230V, DC-13: 5A/24V
	10A gL/gG(NO), 6A gL/gG(NC)
	≤ 30ms
	≤ 20ms
	≤ 100ms
	IEC/EN 60947, IEC 61326-3-1, IEC/EN 61000-6-2, IEC/EN 61000-6-4
	250V AC
	6000V(1.2/50us)
	1500V AC, 1 min
	IEC 60947-1
	10Hz ~ 55Hz, 0.35mm
	III
	2
	IP20
	-20°C ~ +60°C
	-40°C ~ +80°C
	≤ 2000 m
	10×10 ⁶ cycles

	PLe, ISO 13849
	Cat.4, ISO 13849
	20, ISO 13849
	99%, ISO 13849
	164, ISO 13849
	68, ISO 13849
	SIL3, IEC 61508
	SIL CL3, IEC 62061
	1, IEC 62061
	≥ 99%, IEC 62061
	2.03×10 ⁻⁶ /PTI=20 IEC 62061
	2.31×10 ⁻⁹ 1/h, IEC 62061
	0, IEC 60204