

DO
1NO

NPFSR-K51D.HT		DO	
		250V AC	
IEC 61508		SIL3 SC3	
SIS	ESD		
■			
■			
■	□		
■	≤ 100ms		
	≤ 0.5Hz		
IEC 61298-3, IEC/EN 61000-6-2,			
IEC 61326-3-1			
250V AC			
6000V(1			
	18V ~ 32V (24V DC)		
	≤ 1.1W/24V DC/		
	≤ 40mA/24V DC		
	≤ 4ms (测试脉冲周期: ≥ 100 ms)		
	≤ 15Ω		
	DO		
	1NO		
	AgSnO ₂ +Au plating		
	5A/250V AC, 5A/24V DC		
	, 5A		
Proof Test			
	() : ≤ 29Ω		
	() : ≥ 48kΩ		
	: ≤ 35V AC, ≤ 5V DC		
	() : ≤ 10mA AC/DC		
	() : > 5A AC/DC		
	: 0.05A/24V DC		
	: 0.5A/30V DC		
	: ≤ 2s		
	:		
	: 19V ~ 26.5V (24V DC)		
	: ≤ 1.2W/24V DC		
	≤ 300ms		
	≤ 100ms		
	≤ 0.5Hz		
	IEC 61298-3, IEC/EN 61000-6-2,		
	IEC 61326-3-1		
	250V AC		
	6000V(1.2/50us) (/)		
	3000V AC, 1min (/)		

		20 , IEC 61508	
		1 / , IEC 61508	
		60%, IEC 61508	
		SIL3, IEC 61508	
		0, IEC 61508	
		≥ 90%, IEC 61508	
		1.45×10 ⁻⁴ /PTI=20年, IEC 61508	